

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/055030 A2

(51) International Patent Classification⁷: **G06F 3/00**

1-1-410, Nagataminamidai, Minami-ku, Yokohama-shi,
Kanagawa 232-0075 (JP).

(21) International Application Number:
PCT/JP2004/018685

(74) Agent: **YAMADA, Ryuichi**; Toko International Patent Of-
fice, Hasegawa Bldg. 4F, 7-7, Toranomon 3-chome, Mi-
nato-ku, Tokyo 105-0001 (JP).

(22) International Filing Date: 8 December 2004 (08.12.2004)

(25) Filing Language: English

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English

(30) Priority Data:
2003-409150 8 December 2003 (08.12.2003) JP
2003-428471 24 December 2003 (24.12.2003) JP

(71) Applicant (for all designated States except US): **CANON
KABUSHIKI KAISHA** [JP/JP]; 30-2, Shimomaruko
3-chome, Ohta-ku, Tokyo 146-8501 (JP).


(72) Inventors; and

(75) Inventors/Applicants (for US only): **YOSHINAGA,
Hideki** [JP/JP]; 4362-23, Izumicho, Izumi-ku, Yoko-
hama-shi, Kanagawa 245-0016 (JP). **MORI, Hideo**
[JP/JP]; 3-16-41, Gumizawa, Totsuka-ku, Yokohama-shi,
Kanagawa 245-0061 (JP). **OKAMOTO, Hideaki** [JP/JP];

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: DISPLAY APPARATUS



(57) Abstract: A display apparatus includes a substrate having a metal layer, a plurality of scanning signal lines and a plurality of data signal lines which intersect with each other and are disposed on the substrate, a display device which has a display element located at an intersecting position of the scanning and data signal lines and is driven by a voltage signal supplied to the scanning and data signal lines, a plurality of coils disposed in parallel with each other on the substrate, and a circuit for detecting currents passing through the plurality of coils by the action of electromagnetic induction of an electromagnetic wave locally generated at a surface of the display device to determine a generation position of the electromagnetic wave by a position of the coils through which the currents pass. The metal layer as a substrate material is a thin electroconductive metal plate which is flexible and not readily broken.



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.